Cooling System Vacuum Purge & Refill Kit

// 7PCS

Multi-Port Fuel Injection Pressure Tester Kit





The Uniquely Designed Pressure Relief Valve



BLOW CASE: W592 x D261 x H62 (mm)



// 3PCS

The Quick Coupling System

∰ 6 (SET)







12PCS

Oil Pressure Tester Kit

ITEM NO. JGAI0703

testing connection

For Multi-Port Fuel Injection (MFI) system

Applications: American vehicles Ford, Chrysler, GM and etc.





2-1/2" Diameter Gauge (150 PSI / 10 BAR) with Relief Valve, 51" Hose with Quick Coupler



ITEM NO.	JGAI0302
TChook tho	lookage of original radiator

- ck the leakage of original radiator cap and cooling system
- Easy reading 2" diameter pressure gauge with dual scale reading of -76 - 0 cmHg and -1 - 0 bar
- ☐Vacuum leakage test for easy identification and prevent coolant spillage and wastage Eliminates the introduction of bubbles and airlock into
- cooling system and deduct the time for refilling coolant Kit includes a pressure gauge, connector, universal
- rubber cone-shape adapter, cooling hose and air bleeding hose Applications: Almost all type of vehicles

BLOW CASE: W390 x D330 x H100 (mm)



Oil Pressure Tester Kit

JGAI1204

Design to diagnose worn oil pumps and engines, faulty oil pressure switches and warning indicators

Excellent fuel injection pressure test kit assists in identifying and diagnosing low fuel pressure, a faulty

Large, shock protected, easy-reading 3-1/2" diameter fuel pressure gauge with dual scale reading of 0 - 150 psi and 0 - 1000 kPa \square All adapters, gauge and hose assemblies feature a quick coupling system for speedy and efficient

fuel pressure regulator, leaking injectors, fuel leaks and clogged fuel filters

- \square Large, shock protected, easy-reading 2-1/2" diameter gauge with dual calibration 0 150 psi, 0 10 bar
- Gauge head with built-in pressure relief valve for quickly repeating test of oil pressure without removing gauge
- Quick-connect coupler for easy and secure connection
- 51" flexible hose allows easy access hard-to-reach places
- Includes 90° coupling adapter and replacement seals
- 10 screw adapters: R 1/8" DIN 2999, 1/8" x 27 NPT, 1/4" x 18 NPT, 3/8" x 20 UNF, 1/2" x 20 UNF, M10 x 1.0, M12 x 1.5, M14 x 1.5, M16 x 1.5, M18 x 1.5
- Applications: Alfa Romeo, Audi, BMW, Citroën, Daihatsu, Fiat, Ford, Honda, Hyundai, Isuzu, Jaguar, Lada, Lancia, Mazda, Mercedes-Benz, Mitsubishi, Nissan, Opel, Peugeot, Renault, Rover, Saab, Skoda, Subaru, Suzuki, Toyota, Vauxhall, VW, Volvo, Zastava etc.

BLOW CASE: W380 x D310 x H80 (mm)